

SLV15CNK

تقنية :Category

2024 ، نوفمبر، written by Mahdi MILED | 23



Picture Private Copyright WWW.MBSMGROUP.TN

Compressor SLV15CNK.2 50/60Hz 220-240V refrigerant R290
height 199 mm LBP 12 kg displacement 15,28cm³

ATHEN210XL

Compressor SLV15CNK.2. Speed: 2000/2500/3000/4000
rev/minMore features: LBP 12 kg displacement 15.2 cm
frequency:50/60Hz12kg15,28 cm 3Height: 199mmRefrigerant:
R290power at -15°C: 615/792/996/10 228 W power at -20°C:
467/602/759/941 W power at -25°C: 39°C: 39°C: 39°C:
3/509/645/805 W311/402/510/638 Wtension: 22 0-240 V

Technical Details of AHT Athen XL :210 (-) AD	:Version of Chiller
Gross Content: 1177 liters	Manufacturer: AHT
Net Content: 875 liters	Model: Athen 210(-) AD
Display Area: 1,75 m ²	High energy savings compared to conventional compound systems
Ambient Temperature: +16 bis +25 °C	AHT e-conomize: Additional high energy saving potential through comprehensive optimization in technology and design
Temperature Range: -18 °C bis -23 °C	Improved product inspection with optimized usable net content of chiller
Rated Voltage / Normal Frequency: 220 - 240 V / 50 Hz	Ecologically harmless by the natural refrigerant propane
Rated Power Consumption: 450 W	Completely CFC and HFC-free
Rated Power Consumption Light: (ca. 28 W (optional	Secured product quality due to constant internal temperature with high power reserves
Rated Current: 2.0 A	Ready to plug in without installation effort
Protection: 16 A	Low investment and operating costs
Energy Consumption (at 25 °C): 8.7 kWh / 24 h	Refrigeration is maintenance free

Length of Connection Cable: 1750 mm	Large curved glass sliding lid
Refrigerant: R290	
Refrigerant Quantity: 110 g	
Max. Permissible Operating Pressure: 30 bar	
Length (Outside / Inside): 2102 / 1970 mm	
Depth (Outside / Inside): 993 / 860 mm	
Working Height (Front / Outside Height): 800 / 910 mm	
Stacking Height: 600 mm	
Weight (Net): 141 kg	
(Lighting: LED (optional	
Year of construction: 2010 +/- 3 years	

SLV15CNX

معلومات عامة

- الموديل: SLV15CNX LBP R290 inverter blcd
- القدرة الحصانية: عادةً ما يكون تصنيف القدرة الحصانية لهذا الموديل هو **HP 5/8** (حوالي 0.625 HP).

- **النوع:** يُصنف كضاغط ضغط منخفض (LBP)، مما يجعله مناسبًا لتطبيقات التبريد.
- **التوافق:** متوافق مع موديل دانفوس 104H-8568، مما يدل على استخدامه في أنظمة التبريد المختلفة.

الاستخدامات

هذا الضاغط مصمم للكفاءة والموثوقية في إعدادات التبريد التجارية، وخاصةً حيث يتم استخدام غاز التبريد R290. يعد خيارًا جيدًا للمشاريع التي تتطلب أداءً عاليًا في بيئات العمل المختلفة.



ATHEN 240XL(-)ADVS



ATH

Seriennr. 280262 00001780

Gerätedaten
cabinet data

class 3 (25°C/60%RH)

(-)

Nennspannung/frequ. Nom Voltg./frequ.
Tension/Frequence nominale

220-240V/50Hz

Nennaufnahme Nom Consump.
Prise de courant nominale

450 W

Nennstrom Nom Current
Courant nominal

2,0 A

Schutzart Protection class
Type de protection

-

Typ Typ
Type

B 845N

Energieaufnahme Energy consump.
Absorption d'énergie

8,7 kWh/24h

Absicherung Fuse
Protection par fusibles

16 A

Kältemittel(Menge) Refrigerant(Quan)
Type / Quantité de réfrigérant

R290/0,110 kg


Nettoinhalt Net Content
Capacité nette

801 dm³

max. zul. Betriebsüberdruck 30 bar
Eigensicher nach VVV-VBG 20, § 7.3
Dichtheit geprüft

Surpression max. de service
Sécurité propre selon VVV-
Imperméabilité examinée

Subile 30 bar
57.3





Picture Private Copyright WWW.MBSMGROUP.TN